Serial No. 09/508,490

Attorney Docket No.: 20496-248

**LISTING OF CLAIMS:** 

Claim 1. (Currently Amended) A process for the production of a buckling resistant

stove-finished structural component from a cold strip which comprises ageing-sensitive

steel with a high bake-hardening potential, comprising the steps of:

- converting the cold strip by temper rolling to a yield point elongation-free

state in which the condition  $R_{eh} - R_{el} \le 2 \text{ N/mm}^2$  is met,

storing the cold strip at storage temperature below room temperature for a

storage-period whose length is at most equal to the length of the period at whose end the

value of critical ageing is reached which results in dependence on the particular storage

temperature,

- cold working the cold strip to give a structural component, and

stove-finishing the structural component,

wherein said bake-hardening potential is at least 70 N/mm<sup>2</sup>.

Claim 2. (Currently Amended) A process according to claim 1, characterized in

that wherein the storage temperature T in [K] of the cold strip is selected in dependence

on the planned storage time t in [h] in accordance with the equation

T = 9225 / (31.48 - 1n (48t))

with T: storage temperature in [K]

T: storage time in [h].

2

Attorney Docket No.: 20496-248

Claim 3 (Currently Amended) A process for the production of a buckling-resistant stove-finished structural component from a cold strip which comprises ageing-sensitive steel with a high bake-hardening potential, comprising the steps of:

- storing the cold strip undressed for a storage period at room temperature,
- converting the cold strip by temper rolling to a state in which the condition  $R_{\text{eh}}-R_{\text{el}} \leq 2 \; \text{N/mm}^2 \; \text{is met},$
- cold working the temper rolled cold strip to give a structural component, and
- stove-finishing the structural component, wherein said bake-hardening potential is at least 70 N/mm<sup>2</sup>.

Claim 4-5 (Cancelled).